Bowers & Wilkins



Brave the elements

For those who want to bring impeccable Bowers & Wilkins sound quality to places where conventional speakers fear to tread, we've come up with the ideal solution: the AM-1 architectural monitor. This ultra-durable, weather resistant speaker is designed with the outdoors in mind – perfect for patios, gardens and poolsides – but its robust design and sleek looks also make it a great choice for public indoor spaces.

Technical Specifications

Technical features	Nautilus™ tube loaded aluminium dome tweeter Glassfibre cone bass/midrange Auxiliary Bass Radiator (ABR)
Description	2-way system with Auxiliary Bass Radiator (ABR)
Drive units	1x ø25mm (1in) aluminium dome high-frequency 1x ø130mm (5in) glassfibre cone bass/midrange
Frequency range	-6dB at 46Hz and 50kHz (wall mounted)
Frequency response	51Hz - 22kHz on reference axis (wall mounted)
Sensitivity	86dB (2.83V, 1m)
Total harmonic distortion	<1% 200Hz - 20kHz (86dB, 1m)
Nominal Impedance	8V (5.2 V min)
Recommended amplifier power	20W - 100W into 8V on unclipped programme
Dimensions	Height: 310mm (12 1/4in) (Includes wall bracket) Width: 180mm (7in) Depth: 210mm (8 1/4in)
Net weight	4kg (8.8lb)
Finishes	White Black







Bowers & Wilkins

www.bowers-wilkins.com Copyright © B&W Group Ltd. E&OE